63188569 A Page 1 of 2



(11) Publication number:

(71) Applicant: TOYOTA AUTOM L

(72) Inventor: KUSHIBE TETSUAKI

SAKAMOTO KENJI

Generated Document.

PATENT ABSTRACTS OF JAPAN

(21) Application number: **62021380**

(51) Intl. Cl.: **B62D** 5/07

(22) Application date: 31.01.87

(30) Priority:

publication:

(43) Date of application

04.08.88

(84) Designated contracting states:

....

(74) Representative:

(54) FULL-HYDRAULIC TYPE POWER STEERING GEAR

(57) Abstract:

PURPOSE: To enable a simplified structure to correct the position displacement of a steered wheel, by connecting an oil hydraulic pump for power steering to a power cylinder through a correction pressure oil supply line having a solenoid opening and closing valve.

CONSTITUTION: A power cylinder 7 is directly connected to an oil hydraulic pump 4 for power steering through a correction pressure oil supply line 9. This correction pressure oil supply line 9 provides a solenoid opening and closing valve 10 for opening and closing a passage. In this way, when an amount of oil, fed to the power cylinder 7, comes to be insufficient with no agreement of the rotary angle of a handle 1 with the steered angle of a steered wheel 14, the solenoid opening and closing valve 10 is switched to a passage opening side. Then working fluid from the oil hydraulic pump 4 is supplied to the power cylinder 7 via

... ...

the correction pressure oil supply line 9 in a different system from a steering valve unit 3. Accordingly, the position displacement of the steered wheel 14 from the handle 1 can be corrected by a simplified structure.

COPYRIGHT: (C)1988,JPO&Japio

